

Specification for Camera, DVR(CPPLUS XU series) and other peripherals

Sr. No.	Item
1	<p>Detailed Specification of Camera (Minimum-04)</p> <ul style="list-style-type: none"> • D&N Colour 30mtr Variable IR Camera Box IR camera-1/3 in Super HAD CCD with weather proof Housing and Mounting bracket, including SMPS etc. • Signal Processing: Digital signal processing (DSP) • Filter: Dual-window mechanical type, IR Pass, IR Cut • Effective Pixels (H x V) PAL: 752 x 582, NTSC: 768 x 494 • Night-Time Sensitivity 0 lux (infrared on) • Day-Night Switching Photocell-controlled, automatic • Electronics Iris 1/50 to 1/100,000 s (PAL) • 1/60 to 1/100,000 s (NTSC) • Output Signal 1Vpp composite video, 75 ohm • S/N Ratio Greater than 48 dB • Lens Vari focal 2.8 to 10 mm, DC auto-iris • Lens Control Externally adjustable zoom, focus and auto iris • LEDs Even-distribution infrared array, photocell controlled • Wavelength 850 nm • Number of LEDs minimum 24 pcs • Voltage 12 to 24 VDC or VAC • Environmental Designed to IP66 30
2.	<p>Detailed Specifications -DVR 4/8 channel (CPPLUS XU series make)</p> <ul style="list-style-type: none"> • Small File Sizes by H.264 Compression • Various Recording Resolution (704x480,704x240, 352x240) • Up to 120fps@352 X 240 Recording • Default Mouse, IR Remote Controller • User-Friendly GUI • Various Monitor Output • Multi Motion Detection areas • Multi-Channel Video Backup capability • Pre-Alarm Recording • Time and Date Sync from NTP Server • Easy System S/W Update with USB Memory Stick and Network • Multiplex (Simultaneous Live display, Recording, Search, Network, Back-up) • Frame Rate & Quality Adjustment per Individual Camera • Max 16 channels connections via IE browser • VGA output is also required. • Hard Disk built-in SATA 1000GB 1 HDD • Backup Mode HDD backup, USB backup and network download backup • Network Protocols-TCP/IP, UDP, DHCP, DNS, IP • Filter, PPPoE, DDNS, FTP, Alarm Server • Motion Detection - Various sensitivity levels, Alarm can activate record, external alarm or screen message prompt, Video Loss- Can activate external alarm or screen message prompt should support Centralised monitoring system at H.O
3.	<p>Internet Facility</p> <ul style="list-style-type: none"> • Minimum 512 Kbps internet speed • One dedicated static global IP
4.	<p>UPS for Min 30 Min backup (Optional) / Hot line connection</p>